



	(g/m3)	4.85~5.0	4.85~5.0	4.85~5.0	4.85~5.0	4.85~5.0	4.85~5.0	4.85~5.0	4.85~5.0
Anti-fold intensity	(N/m2)	(0.5~0.9) x108	(0.5~0.9) x108	(0.5~0.9) x108	(0.5~0.9) x108	(0.5~0.9) x108	(0.5~0.9) x108	(0.5~0.9) x108	(0.5~0.9) x108
	(Kgf/mm2)	5~9	5~9	5~9	5~9	5~9	5~9	5~9	5~9
Compressed intensity	(N/m2)	>6.9x108	>6.9x108	>6.9x108	>6.9x108	>6.9x108	>6.9x108	>6.9x108	>6.9x108
	(Kgf/mm2)	>70	>70	>70	>70	>70	>70	>70	>70
Cut intensity	(N/m2)	(0.2~0.5) x108	(0.2~0.5) x108	(0.2~0.5) x108	(0.2~0.5) x108	(0.2~0.5) x108	(0.2~0.5) x108	(0.2~0.5) x108	(0.2~0.5) x108
	(Kgf/mm2)	2~5	2~5	2~5	2~5	2~5	2~5	2~5	2~5

Download :  Ferrite Magnet,  Ferrite Magnet



Sintered Hard Ferrite Magnet-28EH



Sintered Hard Ferrite Magnet-30EH



Sintered Hard Ferrite Magnet-33EH



Sintered Ring Ferrite Magnet-LNG12



Sintered Ring Ferrite Magnet-LNG13



Injection Bonded Ferrite Magnet-N30



Injection Bonded Ferrite Magnet-N33



Ferrite Magnet Material-N42H



Ferrite Magnet Material-N44H



Ferrite Magnet Material-N46H



Ferrite Magnet-N38H



Ferrite Magnet-N40H

**Other related category** :NdFeB Magnet,Cast AlNiCo Magnet,SmCo Magnet,Flexible Magnet,Magnetic Assemblies,Rubber Magnet,

## Contact Us

**1.Ningbo YiLi Magnetic Co.,Ltd**

2.Add: Tengyuan village science and technology zone.

3.WebSite: <http://www.MagnetMaterialyl.com>

4. Tel: +86-574-87932448

5. Fax: +86-574-87932448

6. E-Mail: [sales@MagnetMaterialyl.com](mailto:sales@MagnetMaterialyl.com)